

CapTel 880iB Specifications

Physical Dimensions

Size: 9" × 6.5" × 7.5"

Weight: 2 lb. 10 oz.

Power

AC Adapter: 5.9-6V, 2-3 Amps
(barrel is negative)

Adapter is UL listed.

Dial Pad

Large Keys: 0.75" × 0.70"

Display

10.1" Backlit, graphical LCD

color display

1024 × 600 pixels

Function Buttons

3 Programmable Speed Dial

1 Customer Service Speed Dial

Redial

Flash

Mute

Tone

Caption

Volume

Up/Down/Yes/No

Approvals

FCC approved

ACTA Product-Labeling Number:

US:D8KTE00BCAPTEL840

REN: 0.0B

Controls

Conversation: Amplification
when Captions on: 0-40 dB gain
when Captions off: 0-18 dB gain

Tone

Ringer: off, low, medium, high
(0-87 dB at 1 meter)

Indicator Lights

Mute

Volume Levels (1 through 12)

Captions On/Off

Handset

Type: HAC (Hearing Aid
Compatible)

Dialing

Phone Book (97 entries)

Speed Dial (3 entries)

Redial (Last 10 dialed numbers)

Captions

Caption font size:

- Large 0.38"

Adjustable colors for
background and font.

Connections

Telephone line: requires RJ11
connection (can be standard
analog line, VOIP, DSL with filter,
or fiber optic. Does not support
digital PBX system unless analog
port available).

3.5 mm Neckloop/Headset

2.5 mm Headset with microphone

Ethernet connection to Internet

USB connection to Braille display

Bluetooth® Connectivity

AC power

Conversation Memory

500 lines of captions

Answering Machine

63 Recordable messages

(2 minute max per message)

Recordable greeting

Selectable number of rings
before answer

Ability to caption messages left
on an external answering
machine